

# PRODUCT CODE - 2250 MARIDUR PU SURFACER GREY/WHITE(3.1)

## **Description**

Maridur PU Surfacer is essentially meant for vehicle refinishing, which should dry much faster than any synthetic primer.

## **Areas of Application**

All types of vehicles that are to be painted or Any iron or wooden surface needing white topcoat must be covered with white primer surfacer.

#### **Technical Data**

Colour : Grey/ white..

Viscosity : Base: 200± 5 Hardener Surface Dry

: 10 Min at 30 C

Touch Dry : 45-60 Min at 30 °C Hard Dry : Overnight, 30 °C Mixing Ratio - Base: Hardener : 3:1 by Volume Application Method : Conventional Spray

Application Viscosity : 22-25 Seconds by Ford Cup No. F4 at 30 °C

Pot Life :4.0 Hours at 30°C (Pot Life decreases with increase in room

temperature)

Over coating Interval : Minimum 4 Hours Maximum 5 days at 30 °C

### **SURFACE PREPARATION**

**Substrate:** The surface to be painted should be free from dirt, dust, oil, grease, or any other contaminations.

#### APPLICATION CONDITIONS

PU Paints are overly sensitive to moisture and Humidity. High humidity during painting may adversely affect the appearance and performance of PU Paint. Avoid painting PU paint/surfacer/primer when atmospheric Temperature is below 5 °C and humidity is above 80%.

#### **THINNER**

Depending upon application conditions and results to be achieved thinner intake may vary from 5% to 10%. Use PU Thinner No. 099 to thin down the paint to required viscosity.

## PRODUCT CODE - 2250 MARIDUR PU SURFACER GREY/WHITE(3.1)

## SUBSEQUENT COAT

Richwood Superio 2K PU Clear Coat.

### **NOTE**

Stir well. Adjust viscosity for brushing or for spraying. The surface should be puttied and well sanded. Start brushing or spraying.

The Product is for Industrial use only. Product data given here is correct to the best of our knowledge but their accuracy may vary depending upon the quality of the substrate, application parameters and atmospheric conditions affecting the performance of the product. Therefore the users are advised to make their own tests to determine the suitability of products for their own purposes under present conditions. Unless agreed upon in writing, we do not accept any liability for the performance of the product. We hereby disclaim any warranties or representations, liability, including but not limited to negligence, injury, consequential losses or damages arising from the use of the Products as recommended above. Product data are subject to change without notice.

PRODUCT DATA SHEET

ISSUED: JUNE 2020

By Mrigold Paints Pvt Ltd

C-1/10 GIDC Estate, Vallabh Udyog Nagar 388120 Anand, Gujarat INDIA