



PRODUCT CODE - 5008 QUICK DRYING - QD PAINTS

Description

QD PAINT is base on Acrylic / Styrene modified Alkyd resin. Which gives good gloss and fast drying.

Areas of Application

use in new construction as well as for maintenance purpose . It is suitable for interior as well exterior of steel structure.

Surface Preparation

The surface to be painted should be free from dirt, dust, oil, grease or any other contaminations. It should be absolutely dry and free from moisture.

Technical Data

Colour	:A Selected range of colours
Finish	: glossy, Smooth and Free from any surface defects
Density	:1.04±0.02 Kg/Liter
Flash Point	:30 °C
Surface Dry	:5 Minutes at 30 Degree C
Touch Dry	:15 Hours at 30 Degree C
Hard Dry	:Overnight- 8-12 Hours at 30 Degree C
Full Cure	:5 days
Shelf	:One Year when stored in shade below 35 Degree Centigrade.
Service Temperature	:100°C, at higher temperature colour/appearance may change.

Notes

Thinner intake will depend upon application conditions, application method and type of object. Depending upon conditions and results to be achieved thinner intake may vary from 5% to 10%.

The Product is for Industrial use only. Product data given here *is correct to the best of our knowledge but their accuracy may vary depending upon the quality of the substrate, application parameters and atmospheric conditions affecting the performance of the product. Therefore the users are advised to make their own tests to determine the suitability of products for their own purposes under present conditions. Unless agreed upon in writing, we do not accept any liability for the performance of the product. We hereby disclaim any warranties or representations, liability, including but not limited to negligence, injury, consequential losses or damages arising from the use of the Products as recommended above. Product data are subject to change without notice.*

By Mrigold Paints Pvt Ltd

C-1/10 GIDC Estate,
Vallabh Udyog Nagar 388120
Anand, Gujarat
INDIA

PRODUCT DATA SHEET

ISSUED: JUNE 2020