

PRODUCT CODE - 8013
THINNER 111

● **Description**

THINNER 111 is Polyurethane Thinner, it is a mixture of aromatic hydrocarbon, ester and ketones used in polyurethane sealer, primer, clear and pigmented topcoat to obtain consistency for application. Areas of Application

● **Recommended for uses**

Suitable for dilution of all types of solvent base polyurethane sealer, primer, clear and pigmented topcoat.

● **Technical Data**

➤ Color	:	clear and transparent
➤ Odour	:	mild aromatic
➤ Weight per litre	:	0.85 ± 0.02 kg./ltr.
➤ Flash point	:	25 °C

● **Storage & packing**

To be stored in a cool, dry & well-ventilated place away from moisture, heat and direct sunlight.

PACKAGING

1 lt, 5 lt & 20 lt

● **Safety precaution**

EYES - In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

SKIN - Wash skin thoroughly with soap and water or approved Industrial cleaner. **DO NOT USE** solvent or thinners.

INHALATION - Remove to fresh air, loosen collar and keep patient rested.

INGESTION - In case of accidental ingestion **DO NOT INDUCE** VOMITING. Obtain immediate medical attention.

PRODUCT CODE - 8013
THINNER 111

Work only in areas of good ventilation. When used indoors always keep doors and windows fully open during application and drying. When applying for short periods only, a suitable cartridge mask may be worn provided the filter is changed regularly. All respiratory equipment must be suitable for the purpose and meet an appropriate standard approved by the HSE.

When applying paint, it is advisable to wear suitable eye protection
Keep container tightly closed and keep out of reach of children. Do not use or store by hanging on a hook. Do not empty into drains or watercourses.

The Product is for Industrial use only. Product data given here *is correct to the best of our knowledge but their accuracy may vary depending upon the quality of the substrate, application parameters and atmospheric conditions affecting the performance of the product. Therefore the users are advised to make their own tests to determine the suitability of products for their own purposes under present conditions. Unless agreed upon in writing, we do not accept any liability for the performance of the product. We hereby disclaim any warranties or representations, liability, including but not limited to negligence, injury, consequential losses or damages arising from the use of the Products as recommended above. Product data are subject to change without notice.*

By Mrigold Paints Pvt Ltd

C-1/10 GIDC Estate,
Vallabh Udyog Nagar 388120
Anand, Gujarat
INDIA

PRODUCT DATA SHEET

ISSUED: JUNE 2020