

**PRODUCT CODE - 8015**  
**THINNER SOLVENT FOR ENAMEL**

● **Description**

THINNER Solvent For Enamel is enamel Thinner, it is used in Synthetic enamel Primer, clear and pigmented topcoat to obtain consistency for application.

● **Recommended for uses**

Suitable for dilution of all type of solvent base Enamel Primer, clear and pigmented topcoat. Also used before and after painting for cleaning purposes.

● **Technical Data**

➤ Color	:	clear and transparent
➤ Weight per litre	:	0.90 ± 0.02 kg./ltr.
➤ Flash point	:	25 °C

● **Storage & packing**

To be stored in a cool, dry & well-ventilated place away from moisture, heat and direct sunlight.

**PACKAGING**

1 lt, 5 lt & 20 lt

● **Safety precaution**

**EYES** - In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

**SKIN** - Wash skin thoroughly with soap and water or approved Industrial cleaner. **DO NOT USE** solvent or thinners.

**INHALATION** - Remove to fresh air, loosen collar and keep patient rested.

**INGESTION** - In case of accidental ingestion **DO NOT INDUCE VOMITING**. Obtain immediate medical attention.

Work only in areas of good ventilation. When used indoors always keep doors and windows fully open during application and drying. When applying for short periods

**PRODUCT CODE - 8015**  
**THINNER SOLVENT FOR ENAMEL**

only, a suitable cartridge mask may be worn provided the filter is changed regularly. All respiratory equipment must be suitable for the purpose and meet an appropriate standard approved by the HSE.

When applying paint, it is advisable to wear suitable eye protection. Keep container tightly closed and keep out of reach of children. Do not use or store by hanging on a hook. Do not empty into drains or watercourses.

The Product is for Industrial use only. Product data given here *is correct to the best of our knowledge but their accuracy may vary depending upon the quality of the substrate, application parameters and atmospheric conditions affecting the performance of the product. Therefore the users are advised to make their own tests to determine the suitability of products for their own purposes under present conditions. Unless agreed upon in writing, we do not accept any liability for the performance of the product. We hereby disclaim any warranties or representations*, liability, including but not limited to negligence, injury, consequential losses or damages arising from the use of the Products as recommended above. Product data are subject to change without notice.

**By Mrigold Paints Pvt Ltd**  
C-1/10 GIDC Estate,  
Vallabh Udyog Nagar 388120  
Anand, Gujarat  
INDIA

**PRODUCT DATA SHEET**  
ISSUED: JUNE 2020