

**PRODUCT CODE 9001**  
**EUROCOAT NC PUTTY**

● **Description**

Eurocoat N.C Putty is made with gun cotton, alkyd, hard resin and plasticizer in combination with suitable extenders and solvents. Each ingredient has to be thoroughly checked to offer a smooth and free flowing paste, which can be easily applied with a putty knife. Besides, the painter should be able to wet sand within half-hour of application to get silk smooth finish. The right quality is Eurocoat N.C Putty.

● **Areas of Application**

Any mild steel surface, which is dented. Examples: mild steel sheets used for making steel furniture, any cast iron article, which has to be made smooth, and all types of vehicles, which need repainting.

● **Surface Preparation**

The article to be provided must be free from oil, grease and rust. The best way to achieve perfection is to sand blast or adopt 7-tank phosphate system. If for some reason, it is not possible, use rustosan, which removes oil/grease and rust in one operation. Besides, it gives a film of iron-zinc phosphate for better corrosion resistance.

● **Technical Data**

|                         |  |
|-------------------------|--|
| APPEARANCE              | : Smooth grey paste free from lumps.     |
| VISCOSITY(PENETRATION)  | : 310 to 340 penetration by penetrometer |
| APPLICATION             | : By putty knife only.                   |
| THINNER TO BE USED      | : None                                   |
| DRYING TIME : Touch dry | : 5 minutes Hard dry : 30-40 minutes     |
| SANDING (WET) TIME      | : 30-40 minutes                          |

● **Directions for Use**

Prepare the surface as directed above. Take a small quantity of the paste on a putty spatula and start filling dents with semicircular motion of hand. Ensure that putty does not roll back. Since the putty contains about 40% of solvents, which go into air, dents will never get filled up in one operation. Minimum three coats of putty are needed to get a desired result. The putty can be applied wet on wet but it is recommended that a minimum time of half an hour be given between each coat so that pinholes do not develop. Start wet cutting using the finest paper and continue till a silky smooth surface is achieved.

● **Notes**

After using the putty, close the lid of the container very tightly. Otherwise, drying will waste half the quantity.

**PRODUCT CODE 9001  
EUROCOAT NC PUTTY**

The Product is for Industrial use only. Product data given here *is correct to the best of our knowledge but their accuracy may vary depending upon the quality of the substrate, application parameters and atmospheric conditions affecting the performance of the product. Therefore the users are advised to make their own tests to determine the suitability of products for their own purposes under present conditions. Unless agreed upon in writing, we do not accept any liability for the performance of the product. We hereby disclaim any warranties or representations, liability, including but not limited to negligence, injury, consequential losses or damages arising from the use of the Products as recommended above. Product data are subject to change without notice.*

**By Mrigold Paints Pvt Ltd**

C-1/10 GIDC Estate,  
Vallabh Udyog Nagar 388120  
Anand, Gujarat  
INDIA

**PRODUCT DATA SHEET**

ISSUED: JUNE 2020